



BEST AND STEADY SELLER

3 inch POS Printer SRP-350II

BIXOLON SRP-350II is a 3 inch thermal POS printer to provide all you need. It supports a printing speed of 200mm/sec. Smart Windows driver and other various drivers make the SRP-350II even more attractive and special. The SRP-350II offers simplicity for operator with Easy-paper-loading and ease of USB 2.0 connectivity with interchangeable interfaces and industry standard drivers.



HIGHLIGHTS



Reliable Printing Performance

- A family of the world-class SRP-350 line
- Printing speed up to 200 mm/sec



BIXOLON[®]
a Better Solution for your Business[™]

3 inch POS Printer
SRP-350II

BIXOLON®



SPECIFICATIONS

Print Characteristics

Print Method

Direct Thermal

Print Speed

200 mm/sec

Print Resolution

180 dpi

Print Width

Up to 72 mm

Sensor

Paper End, Paper Near End, Cover Open

Media Characteristics

Media Type

Receipt

Media Width

80 mm

Media Roll Diameter

Up to 83 mm

Media Thickness

0.062 ~ 0.075 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H)

145 x 203 x 146 mm

(5.70 x 7.99 x 5.74 inch)

Weight

1.65 kg (3.63 lbs.)

Power

EnergyStar Certified,

External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port

2 ports (via y-type adaptor)

Performance Characteristics

Memory

64 Mbit SDRAM, 16 Mbit FlashROM

NV Image Memory

256 Kbytes (mono)

128 Kbytes (color)

Receive Buffer

4 Kbytes

User Define Buffer

12 Kbytes

Interface

USB V2.0 HS, Serial, Parallel, Ethernet

Environment Characteristics

Temperature

Operating: 0 ~ 45°C (32 ~ 113°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

Reliability

Printer Unit (MCBF)

70 Million Lines

TPH

150 km

Auto Cutter

1.8 Million Cuts

Software

Emulation

BXL / POS

Driver / Utility

Windows Driver, OPOS Driver, JPOS

Driver, Linux CUPS Driver, Mac Driver,

Virtual COM USB/Ethernet Driver, Utility Program

SDK

iOS SDK, Android SDK

Fonts / Graphics / Symbologies

Character Size

Font A: 12x24 Font B: 9x17 Font C: 9x24

KOR, CHN, JPN: 24x24

Characters Per Line

Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

Character Sets

Alphanumeric: 95

Extended Graphics: 128x37 page

International: 32

Graphics

Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies

1D: Coda Bar, Code39, Code93, Code128,

EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: PDF417, QR Code

BR-SRP-350II-EN-MAR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

ANY CHANGE RESERVED



SIGMA ELECTRONIC SA

GÜTERSTRASSE 27 / P.O. BOX 1119

CH - 2501 BIEL-BIENNE / SWITZERLAND

TEL: +41 32 322 9177 / FAX: +41 32 323 1756

www.sigma-electronic.com info@sigma-electronic.com