

Epson

TM-T20II

Thermal Printer



- Ideal for customers with low volume of POS transactions
- Cost-saving option for use with Virtual Terminal applications
- All-in-one-box accessories and software
- Printing up to 150 mm/second
- Integrated power supply
- Ease-of-use features including drop-in paper loading, auto-cutter and status LEDs
- Low power consumption, ENERGY STAR® qualified



The TM-T20II can also be placed vertically on counter.

Epson's cost-effective TM-T20II thermal printer is the latest addition to Epson's line of energy-efficient POS printers. Ideal for low-volume retailers, it combines basic POS printing functionality with high reliability and multiple ease-of-use features.

Quality you can count on

The TM-T20 is the ideal choice for retailers with a low volume of POS transactions. Based on Epson's advanced printing technology, it delivers the quality and reliability that Epson is known for, which ensures an easy, reliable printing solution for end users.

All-in-one-box convenience

The TM-T20 comes with everything you need in one box for quick setup and installation. The box includes manuals, drivers, utilities, cables, integrated power supply and easy-to-use software tools to speed programming. In addition, the TM-T20 is available with a USB or Serial interface.

Easy to use. Easy to maintain.

The TM-T20 comes with multiple ease-of-use features from drop-in paper loading and auto-cutter to status LEDs and more. And it also offers optional printer placements

including horizontal or upright for front receipt dispensing or vertical wall placement using a special hanging bracket.

Features Epson reliability

With a MCBF of 60 million lines, a MTBF of 360,000 hours and an auto-cutter life of 1.5 million cuts, the TM-T20 delivers the reliability customers expect from Epson.

ENERGY STAR qualified

Epson's TM-T20 is ENERGY STAR qualified and RoHS compliant and features very low power consumption to reduce costs.

Backed by the leader

The TM-T20 is backed by Epson's industry-leading service and support programs and comes with a two-year limited warranty. To find out more about why the TM-T20 meets all the needs of low-volume retailers.

Epson **TM-T20II** Thermal Printer

Printer Specifications		TM-T20II
General	Print method	Thermal line printing
	Print font	
	Font	9 x 17 and 12 x 24 dots/character (W x H)
	Column capacity	Standard: Paper width 80mm: 48/64; Paper width 58mm: 35/46 42 Column Mode: Paper width 80mm: 42/60; Paper width 58mm: 42/31
	Character size	0.88 x 2.13 and 1.25 x 3 mm (W x H)
	Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic. Barcode: UPC-A, UPC-E, JAN13 (EAN13), JAN8 (EAN), CODE39, ITF, CODABAR (NW-7), CODE93, CODE128, GS1-128, GS1 DataBar. Two-dimensional code: PDF417, QRCode, MaxiCode, 2D GS1, DataBar, Composite Symbology
	Characters per inch	22.6 and 16.9 cpi
Printer	Interface	USB, Serial
	Print speed	Max. 150 mm/sec (5.91 in/sec)
	Paper dimensions	80mm: 3.13" ± 0.02" x 3.27" diameter (79.5 ± 0.5(W) x 83mm) 58mm: 2.26" ± 0.02" x 3.27" diameter (57.5 ± 0.5(W) x 83mm)
	Power	100 – 240V AC, 50/60 Hz
	Power consumption	Approx. 1.0A
	Power supply	Internal (AC cable included)
	D.K.D. function	2 drivers
	Reliability	
	MTBF	360,000 hours
	MCBF	60,000,000 lines
	Autocutter	1.5 million cuts
	Overall dimensions	5.51" x 7.83" x 5.75" (140 x 199 x 146 mm) (W x D x H)
	Mass	3.75lb (1.7 kg)
	Color	Epson Dark Gray, Epson Cool White
	Standard accessories	Roll paper x 1 roll (for checking the initial movement of the printer), CD-ROM, power switch cover, power switch waterproof cover, wall hanging bracket, screws for wall hanging bracket, rubber feet for vertical installation, switch panel for vertical installation, 58mm width paper guide plate, interface cable (USB only), AC cable
	Safety standards	UL/CSA/EN/TUV/GOST-R
	Installation	Horizontal/vertical on counter/vertical on wall with wall hanging bracket
Warranty	2 year limited	

Options

Affixing tape and external buzzer unit

Inch values are approximate.

EPSON[®]
EXCEED YOUR VISION



ANY CHANGE RESERVED



SIGMA ELECTRONIC SA

GÜTERSTRASSE 27 / P.O. BOX 1119

CH - 2501 BIEL-BIENNE / SWITZERLAND

TEL: +41 32 322 9177 / FAX: +41 32 323 1756

www.sigma-electronic.com info@sigma-electronic.com