

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOLYKOTE(R) TP-42 PASTE
Product code : 000000000002209942

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricants and lubricant additives

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe

Telephone : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163

E-mail address of person responsible for the SDS : sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350
Dow Corning (Wiesbaden 24h) Tél: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling

EUH210 Safety data sheet available on request.

2.3 Other hazards

None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Inorganic and organic compounds
Mixture

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Calcium hydroxide	1305-62-0 215-137-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 30 - < 50
White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27	Asp. Tox. 1; H304	>= 20 - < 30
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5 265-155-0 649-465-00-7	Asp. Tox. 1; H304	>= 1 - < 10
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0 265-169-7 649-474-00-6	Asp. Tox. 1; H304	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Metal oxides
Carbon oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

7.3 Specific end use(s)

- Specific use(s) : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Calcium hydroxide	1305-62-0	TWA	5 mg/m ³	91/322/EEC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version
1.8

Revision Date:
21.03.2017

SDS Number:
523982-00009

Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Further information	Existing scientific data on health effects appear to be particularly limited, Indicative			
		TWA	5 mg/m ³	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Paraffin waxes and Hydrocarbon waxes	8002-74-2	TWA (Fumes)	2 mg/m ³	GB EH40
Further information	The word 'fume' is often used to include gases and vapours. This is not the case for exposure limits where 'fume' should normally be applied to solid particles generated by chemical reactions or condensed from the gaseous state, usually after volatilisation from melted substances. The generation of fume is often accompanied by a chemical reaction such as oxidation or thermal breakdown.			
		STEL (Fumes)	6 mg/m ³	GB EH40
Further information	The word 'fume' is often used to include gases and vapours. This is not the case for exposure limits where 'fume' should normally be applied to solid particles generated by chemical reactions or condensed from the gaseous state, usually after volatilisation from melted substances. The generation of fume is often accompanied by a chemical reaction such as oxidation or thermal breakdown.			

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Calcium hydroxide

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium hydroxide	Workers	Inhalation	Acute local effects	4 mg/m ³
	Workers	Inhalation	Long-term local effects	1 mg/m ³
	Consumers	Inhalation	Acute local effects	4 mg/m ³
	Consumers	Inhalation	Long-term local effects	1 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium hydroxide	Fresh water	0.49 mg/l
	Marine water	0.32 mg/l
	Intermittent use/release	0.49 mg/l
	Sewage treatment plant	3 mg/l
	Soil	1080 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	Oral (Secondary Poisoning)	9.33 mg/kg food
Distillates (petroleum), solvent refined heavy naphthenic	Oral (Secondary Poisoning)	9.33 mg/kg food

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Personal protective equipment

- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Hand protection
Remarks : Wash hands before breaks and at the end of workday.
- Skin and body protection : Skin should be washed after contact.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapour type (A-P)
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : paste
- Colour : white
- Odour : none
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : 160 °C
Method: closed cup
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Not classified as a flammability hazard
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : Not applicable
- Relative vapour density : No data available
- Relative density : 1.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

Particle size : No data available

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Calcium hydroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Species: Rabbit
Result: No skin irritation
Remarks: On basis of test data.

Components:

Calcium hydroxide:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation

White mineral oil (petroleum):

Species: Rabbit
Result: No skin irritation

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit
Result: No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Species: Rabbit
Result: No eye irritation
Remarks: On basis of test data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Components:

Calcium hydroxide:

Species: Rabbit
Method: OECD Test Guideline 405
Result: Irreversible effects on the eye

White mineral oil (petroleum):

Species: Rabbit
Result: No eye irritation

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit
Result: No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation
Remarks: Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Germ cell mutagenicity

Not classified based on available information.

Components:

Calcium hydroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

: Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

: Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Calcium hydroxide:

Species: Rat
Application Route: Ingestion
Exposure time: 104 weeks
Result: negative
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Species: Rat
Application Route: Ingestion
Exposure time: 24 Months
Result: negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

Components:

Calcium hydroxide:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Result: negative
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

Components:

Calcium hydroxide:

Assessment: May cause respiratory irritation.

Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species: Rat
LOAEL: > 160 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Species: Rat
LOAEL: >= 1 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Method: OECD Test Guideline 412

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rat
NOAEL: > 0.98 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 Days

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 4 Weeks
Method: OECD Test Guideline 410
Remarks: Based on data from similar materials

Species: Rat
NOAEL: > 980 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated heavy naphthenic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

garded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Calcium hydroxide:

- Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 49.1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC10 (Pseudokirchneriella subcapitata (green algae)): 79.22 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 : 300.4 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l
Exposure time: 14 d

White mineral oil (petroleum):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 1,000 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,000 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC : \geq 1.93 mg/l
Exposure time: 10 min

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Water Accommodated Fraction

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC : > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8	Revision Date: 21.03.2017	SDS Number: 523982-00009	Date of last issue: 21.11.2016 Date of first issue: 27.08.2014
----------------	------------------------------	-----------------------------	---

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

- KECI : All ingredients listed, exempt or notified.
- TCSI : All ingredients listed or exempt.
- REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
- AICS : All ingredients listed or exempt.
- IECSC : All ingredients listed or exempt.
- ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.
- PICCS : All ingredients listed or exempt.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- TSCA : Clearance for manufacture, import, processing, or use of this product under the United States Toxic Substances Control Act (TSCA) is based on a low volume exemption (LVE) from the Inventory listing requirements of TSCA (40 CFR 723.50(c) (1)).
- NZIoC : All ingredients listed or exempt.

Additional regulatory information

9-Octadecenyl-13-docosenate 17673-56-2

TSCA clearance for manufacture, import, processing, or use of this product is based on a low volume exemption from the Inventory listing requirements of TSCA (40 CFR 723.50(c) (1)). For activities regulated by TSCA, the following conditions apply: The LVE substance contained in the product may only be used as a lubricant. The low volume exemption specifies that processors and industrial users of this product will control exposure by using pumping and application apparatus for transfer and use whenever possible, and will landfill spent product containers.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version 1.8 Revision Date: 21.03.2017 SDS Number: 523982-00009 Date of last issue: 21.11.2016
Date of first issue: 27.08.2014

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Skin Irrit. : Skin irritation
STOT SE : Specific target organ toxicity - single exposure
91/322/EEC : Europe. Commission Directive 91/322/EEC on establishing indicative limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
91/322/EEC / TWA : Limit Value - eight hours
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

DOW CORNING

MOLYKOTE(R) TP-42 PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 21.11.2016
1.8	21.03.2017	523982-00009	Date of first issue: 27.08.2014

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN