Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) Issue date: 18/08/2020 Version: 1.0

SDS No: 12236-0037

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : WF5

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Cleaner

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Greiner Vibrograf AG Mittelstrasse 2 4900 Langenthal

T +41 62 916 60 80 - F +41 62 916 60 81

1.4. Emergency telephone number

Emergency number : England & Wales: 111, Scotland: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)









GHS02

GHS07

GHS08

GHS09

Signal word (CLP)

Danger

Contains

: Naphtha (petroleum), hydrodesulfurized heavy; Solvent naphtha (petroleum), light arom.; 1-methoxy-2-propanol; monopropylene glycol methyl ether; Isopropanol

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smokina.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

Extra phrases : Restricted to professional users.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), hydrodesulfurized heavy (Note P)	(CAS-No.) 64742-82-1 (EC-No.) 265-185-4 (EC Index-No.) 649-330-00-2	75 - 100	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Solvent naphtha (petroleum), light arom. (Note P)	(CAS-No.) 64742-95-6 (EC-No.) 918-668-5 (REACH-no) 01-2119455851-35	2,5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (REACH-no) 01-2119457558-25	≥ 10 – < 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1-methoxy-2-propanol; monopropylene glycol methyl ether Substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB)	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3 (REACH-no) 01-2119457435-35	2,5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
ammonium hydroxide	(CAS-No.) 1336-21-6 (EC-No.) 215-647-6 (EC Index-No.) 007-001-01-2	1 - 2,5	Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Acute 1, H400

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
ammonium hydroxide	(CAS-No.) 1336-21-6 (EC-No.) 215-647-6 (EC Index-No.) 007-001-01-2	(5 ≤C < 100) STOT SE 3, H335

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3

Full text of H-statements: see section 16

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SDS No: 12236-0037

SECTION 4: First aid measures

First-aid measures after skin contact

4.1. Description of first aid measures

First-aid measures general : Take off immediately all contaminated clothing. In the event of persistent symptoms receive

medical treatment. Take affected person away from danger area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If symptoms persist, call a

physician. In case of loss of conscience place the victim in the recovery position.

: Wash off immediately with soap and plenty of water. Treat subsequently with skin cream.

Get medical advice if skin irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult an ophthalmologist if irritation persists.

First-aid measures after ingestion : Attention. Beware, danger of aspiration. Do not induce vomiting. Call a physician

immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and

vomiting.

Symptoms/effects after skin contact : Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing

properties of the product.

: May cause eye irritation.

Symptoms/effects after ingestion : Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Symptoms/effects after eye contact

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Hydrogen chloride. Carbon oxides (CO, CO2). Phosgene.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus.

Other information : Vapours are heavier than air and may spread along floors. The vapour/air mixture is

explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray

jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No flames, no sparks. Eliminate all sources of ignition. Evacuate

unnecessary personnel. Wear personal protective equipment.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Printing date: 19/08/2020 GB - en 3/11

according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal Methods for cleaning up

binding agents). Take up mechanically (sweeping, shovelling) and collect in suitable

container for disposal.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Explosion free apparatus

have to be used. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Vapours are heavier than air and may spread along floors. Avoid formation of

aerosols.

Hygiene measures : Do not inhale vapour. Do not eat, drink or smoke when using this product. Always wash

hands after handling the product. Treat subsequently with skin cream. Avoid contact with

skin, eyes and clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to

explosion protection guidelines.

Incompatible products Oxidizing agent.

Information on mixed storage Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)		
EU - Occupational Exposure Limits		
Local name	White spirit Type 1	
IOELV TWA (mg/m³)	116 mg/m³	
IOELV TWA (ppm)	20 ppm	
IOELV STEL (mg/m³)	290 mg/m³	
IOELV STEL (ppm)	50 ppm	
Notes	Skin. (Year of adoption 2007)	
Regulatory reference	SCOEL Recommendations	

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
EU - Occupational Exposure Limits		
Local name	1-Methoxypropanol-2	
IOELV TWA (mg/m³)	375 mg/m³	
IOELV TWA (ppm)	100 ppm	
IOELV STEL (mg/m³)	568 mg/m³	
IOELV STEL (ppm)	150 ppm	
Notes	Skin	

according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	1-Methoxypropan-2-ol	
WEL TWA (mg/m³)	375 mg/m³	
WEL TWA (ppm)	100 ppm	
WEL STEL (mg/m³)	560 mg/m³	
WEL STEL (ppm)	150 ppm	
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
WEL chemical category	Potential for cutaneous absorption	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Isopropanol (67-63-0)		
United Kingdom - Occupational Exposure Limits		
Local name	Propan-2-ol	
WEL TWA (mg/m³)	999 mg/m³	
WEL TWA (ppm)	400 ppm	
WEL STEL (mg/m³)	1250 mg/m³	
WEL STEL (ppm)	500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Pay attention to explosion protection guidelines.

Hand protection:

Protective gloves. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Neoprene	6 (> 480 minutes)	0,75		EN ISO 374, EN 388
Chemically resistant protective gloves	Polyvinylchloride (PVC)	6 (> 480 minutes)	1,3		EN ISO 374, EN 388

Eye protection:

Protective goggles (EN 166)

Skin and body protection:

Solvent-resistant protective clothing

Respiratory protection:

Wear respiratory protection.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

Device	Filter type	Condition	Standard
Breathing apparatus with filter		Short term exposure	
Self contained breathing apparatus		Long term exposure	

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Slightly yellowish.
Odour : ammonia.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : $150 \,^{\circ}\text{C}$ Flash point : $40 \,^{\circ}\text{C}$

Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : Not applicable Vapour pressure : 2.1 hPa (20°C) Relative vapour density at 20 °C : No data available Relative density : No data available : 0.802 g/cm3 (20°C) Density : Water: Not miscible Solubility Log Pow : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available

Explosive properties : Product is not explosive. Flammable or explosive vapour/air mixtures may be formed.

Oxidising properties : Not self-igniting.

Lower explosive limit (LEL) : 0.6 vol %

Upper explosive limit (UEL) : 7 vol %

9.2. Other information

 VOC content
 : 92.8 %

 Solvent content
 : 14,3 %

 Ignition temperature
 : 507 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

No data available.

10.3. Possibility of hazardous reactions

alkali metals.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited.

according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2). Phosgene. Hydrogen chloride.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Solvent naphtha (petroleum), light arom. (64742-95-6)	
LD50 oral rat 2000 – 5000 mg/kg	
ATE CLP (oral) 2000 mg/kg bodyweight	

Skin corrosion/irritation : Causes skin irritation.

: Causes serious eye irritation. Serious eye damage/irritation

Respiratory or skin sensitisation : Not classified : Not classified Germ cell mutagenicity : Not classified Carcinogenicity

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term

(acute) Hazardous to the aquatic environment, long-term : Not classified

: Toxic to aquatic life with long lasting effects.

(chronic)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Do not flush into surface water or sewer system

according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Do not discharge into drains.

: Must not be disposed together with household garbage. Empty containers should be taken for local recycling, recovery or waste disposal. Packaging that cannot be cleaned should be

disposed of like the product.

European List of Waste (LoW) code : 16 05 08* - discarded organic chemicals consisting of or containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shipping	g name			
FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)	Flammable liquid, n.o.s. (Solvent naphtha (petroleum), light arom.)	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)
Transport document descri	ption			
UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1993 Flammable liquid, n.o.s. (Solvent naphtha (petroleum), light arom.), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), ligh arom.), 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard c	lass(es)			
3	3	3	3	3
3	1 1 1 1 1 1 1 1 1 1	3	**************************************	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental haz	ards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1 Special provisions (ADR) 274, 601 Limited quantities (ADR) 51 : E1 Excepted quantities (ADR)

: P001, IBC03, LP01, R001 Packing instructions (ADR)

Mixed packing provisions (ADR) MP19 Transport category (ADR) 3 : 30 Hazard identification number (Kemler No.)

according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

Orange plates 30 1993

Tunnel restriction code (ADR) : D/E EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 223, 274, 955

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : LP01, P001 EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-E

Air transport

: E1 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L PCA packing instructions (IATA) : 355 PCA max net quantity (IATA) : 60L CAO packing instructions (IATA) 366 CAO max net quantity (IATA) : 220L Special provisions (IATA) : A3 ERG code (IATA) 3L

Inland waterway transport

: F1 Classification code (ADN) : 274, 601 Special provisions (ADN) Limited quantities (ADN) : 5 L Excepted quantities (ADN) : E1 Equipment required (ADN) : PP, EX, A Ventilation (ADN) : VE01 Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1 Special provisions (RID) : 274, 601 Limited quantities (RID) : 5L : E1 Excepted quantities (RID)

: P001, IBC03, LP01, R001 Packing instructions (RID)

: 3 Transport category (RID) Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 92.8 %

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) SDS No: 12236-0037

Full text of H- and EUH-statements:			
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis		
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H400	Very toxic to aquatic life.		
H411	Toxic to aquatic life with long lasting effects.		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Flam. Liq. 3	H226	On basis of test data	
Skin Irrit. 2	H315	Calculation method	
Eye Irrit. 2	H319	Calculation method	
STOT SE 3	H336	Calculation method	
Asp. Tox. 1	H304	Expert judgment	
Aquatic Chronic 2	H411	Calculation method	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.