







Max. load weight «G» for different lift combinations

Method of lift									
Number of legs	1	1	2	2	2		3 - 4		
Angle of inclination	0°	90°	0°	90°	0 - 45°	45 - 60°	0 - 45°	45 - 60°	
Thread d1	M4	0.05	0.05	0.1	0.1	0.07	0.05	0.105	0.05
	M5	0.075	0.075	0.15	0.15	0.1	0.075	0.158	0.075
	M6	0.1	0.1	0.2	0.2	0.14	0.1	0.21	0.1
	M8	0.3	0.3	0.6	0.6	0.4	0.3	0.6	0.3
	M10	0.6	0.6	1.2	1.2	0.8	0.6	1.3	0.6
	M12	1	1	2	2	1.4	1	2.1	1
	M14	1.3	1.3	2.6	2.6	1.8	1.3	2.7	1.3
	M16	1.6	1.6	3.2	3.2	2.2	1.6	3.4	1.6
	M18	2	2	4	4	2.8	2	4.2	2
	M20	2.5	2.5	5	5	3.5	2.5	5.3	2.5
	M22	3	3	6	6	4.2	3	6.3	3
	M24	4	4	8	8	5.6	4	8.4	4
	M27	5	5	10	10	7	5	10.5	5
	M30	6.3	6.3	12.6	12.6	8.8	6.3	13.2	6.3
	UNC 5/16"	0.29	0.29	0.58	0.58	0.41	0.29	0.61	0.29
	UNC 3/8"	0.54	0.54	1.08	1.08	0.76	0.54	1.14	0.54
	UNC 1/2"	0.99	0.99	1.99	1.99	1.37	0.99	2.09	0.99
	UNC 5/8"	1.72	1.72	3.44	3.44	2.41	1.72	3.61	1.72
	UNC 3/4"	2.49	2.49	4.98	4.98	3.49	2.49	5.23	2.49
	UNC 7/8"	2.99	2.99	5.98	5.98	4.19	2.99	6.28	2.99