







Max. load weight «G» for different lift combinations

Method of lift									
Number of legs	1	1	2	2	2		3 - 4		
Angle of inclination	0°	90°	0°	90°	0 - 45°	45 - 60°	0 - 45°	45 - 60°	
Thread d1	M8	0.8	0.5	1.6	1	0.7	0.5	1.05	0.5
	M10	1.6	0.7	3.2	1.4	0.98	0.7	1.47	0.7
	M12	1.9	0.9	3.8	1.8	1.26	0.9	1.89	0.9
	M16	3.2	1.8	6.4	3.6	2.52	1.8	3.78	1.8
	M20	6.5	2.7	13	5.4	3.78	2.7	5.67	2.7
	M24/3.8t	8	3.8	16	7.6	5.32	3.8	7.98	3.8
	M24/4.2t	7	4.2	14	8.4	5.88	4.2	8.82	4.2
	M30	10	6.3	20	12.6	8.82	6.3	13.23	6.3
	M36	12	11	24	22	15.4	11	23.1	11
	M42	15	15	30	30	21	15	31.5	15
	M48	18	16	36	32	22.4	16	33.6	16
	UNC 3/8"	1.59	0.68	3.18	1.36	0.95	0.68	1.43	0.68
	UNC 1/2"	1.9	0.88	3.81	1.77	1.24	0.88	1.86	0.88
	UNC 5/8"	3.18	1.81	6.36	3.63	2.54	1.81	3.81	1.81
	UNC 3/4"	6.81	2.68	13.63	8.1	3.75	2.68	5.63	2.68
	UNC 1"	6.81	4.22	13.63	8.45	5.91	4.22	8.87	4.22
	UNC 1 1/4"	10	6.27	20	12.54	8.78	6.27	13.17	6.27
	UNC 1 1/2"	11.36	11.36	22.72	22.72	15.9	11.36	23.86	11.36