

# Poids max. transportable «G» en «t» pour différents types d'élingage

Type d'élingage / Disposition des points de suspension



Nombre de brins		1	1	2	2	2		3 - 4	
Angle d'inclinaison		0°	90°	0°	90°	0 - 45°	45 - 60°	0 - 45°	45 - 60°
Filet d1	M8	0.8	0.5	1.6	1	0.7	0.5	1.05	0.5
	M10	1.6	0.7	3.2	1.4	0.98	0.7	1.47	0.7
	M12	1.9	0.9	3.8	1.8	1.26	0.9	1.89	0.9
	M16	3.2	1.8	6.4	3.6	2.52	1.8	3.78	1.8
	M20	6.5	2.7	13	5.4	3.78	2.7	5.67	2.7
	M24	7	4.2	14	8.4	5.88	4.2	8.82	4.2
	M30	10	6.3	20	12.6	8.82	6.3	13.23	6.3
	M36	12	11	24	22	15.4	11	23.1	11
	UNC 3/8"	1.59	0.68	3.18	1.36	0.95	0.68	1.43	0.68
	UNC 1/2"	1.9	0.88	3.81	1.77	1.24	0.88	1.86	0.88
	UNC 5/8"	3.18	1.81	6.36	3.63	2.54	1.81	3.81	1.81
	UNC 3/4"	6.81	2.68	13.63	8.45	3.75	2.68	5.63	2.68
	UNC 1"	6.81	4.22	13.63	8.45	5.91	4.22	8.87	4.22
	UNC 1 1/4"	10	6.27	20	12.54	8.78	6.27	13.17	6.27