

Poids max. transportable «G» en «t» pour différents types d'élingage

Type d'élingage / Disposition des points de suspension



Nombre de brins		1	1	2	2	2		2	3 / 4		3 / 4
Angle d'inclinaison		0°	90°	0°	90°	0-45°	45-60°		0-45°	45-60°	unsym.
Filet d1	M36	15.0	8.0(10.0)	30.0	16.0(20.0)	11.2(14.0)	8.0(10.0)	8.0(10.0)	16.8(21.0)	12.0(15.0)	8.0(10.0)
	M42	17.0	12.0(13.0)	34.0	24.0(26.0)	16.8(18.0)	12.0(13.0)	12.0(13.0)	25.2(27.3)	18.0(19.5)	12.0(13.0)
	M48	18.0	13.0(16.0)	36.0	26.0(32.0)	18.2(22.4)	13.0(16.0)	13.0(16.0)	27.3(33.6)	19.5(24.0)	13.0(16.0)
	M56	28.0	16.0(22.0)	56.0	32.0(44.0)	22.4(30.8)	16.0(22.0)	16.0(22.0)	33.6(46.2)	24.0(33.0)	16.0(22.0)
	M64	28.0	16.0(25.0)	56.0	32.0(50.0)	22.4(35.0)	16.0(25.0)	16.0(25.0)	33.6(52.5)	24.0(37.5)	16.0(25.0)