









Max. Transportgewicht «G» in «t» bei verschiedenen Anschlagarten

Anschlagart / Anordnung der Aufhängung											
Strangzahl		1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4
Neigungswinkel		0°	90°	0°	90°	0 - 45°	45 - 60°		0 - 45°	45 - 60°	unsym.
Gewinde d1	M 8	0.63	0.63	1.26	1.26	0.88	0.63	0.63	1.32	0.95	0.63
	M10	0.9	0.9	1.8	1.8	1.3	0.9	0.9	1.9	1.35	0.9
	M12	1.35	1.35	2.7	2.7	1.9	1.35	1.35	2.8	2	1.35
	M16	2	2	4	4	2.8	2	2	4.2	3	2
	M20	3.5	3.5	7	7	4.9	3.5	3.5	7.4	5.25	3.5
	M24	4.5	4.5	9	9	6.3	4.5	4.5	9.5	6.75	4.5
	M30	6.7	6.7	13.4	13.4	9.4	6.7	6.7	14.2	10	6.7
	M36/8t	8	8	16	16	11.2	8	8	16.8	12	8
	M42/10t	10	10	20	20	14	10	10	21	15	10
	M42/15t	15	15	30	30	21	15	15	31.5	22.5	15
	M48	20	20	40	40	28	20	20	42	30	20